

FPHD-11

NUMBER OF PISTONS
11

PISTON DIAMETER
29 mm

SCALING WIDTH
250 mm



PNEUMATIC DECK SCALER

Teryair Pneumatic Deck Scalers are perfect for preparation of floor surfaces. These machines are ideally used for removal of floor coating like paint, chemical & corrosion. Pistons are tungsten tipped & easily replaceable.



Approvals and Certifications

All Teryair pneumatic deck scalers are CE marked and manufactured under an ISO 9001:2015 Quality system – SGS.

Main features for FPHD-11 Pneumatic Deck Scaler

- Compact design
- Low Air Consumption
- Powerful Piston action at 2200bpm per piston
- Large Rear wheels aids manoeuverability
- 3 Point Vibrating Dam System reduces operator fatigue

Applications for FPHD-11 Pneumatic Deck Scaler

- Preparation of floor surfaces.
- Removal of floor coatings like paint, chemical & corrosion

Technical Data

| Teryair Model No | | FPHD11 |
|----------------------------|---------------------|------------------------------|
| Maximum operating pressure | | 6kg/cm ² (90 psi) |
| Air Consumption (No Load) | CFM | 70 |
| | m ³ /min | 1.98 |
| Working width | (mm) | 250 |
| Height | (mm) | 1290 |
| Blows per min | (BPM) | 2200x11 |
| Sound Power Level (Load) | LwA db(A) | 97 |
| Vibration Level Primary | m/s ² | 5.0 |
| Mass (Weight) | Kg | 70 |
| Thread Size of Air Inlet | | 3/4" BSP |