

3SC TRIPLE SCABBLER

NUMBER OF PISTONS
3

PISTON DIAMETER
27 mm

WEIGHT
5.7 kgs



3SC

TRIPLE SCABBLER

Teryair Pneumatic Scabbling Hammers remove heavy rust and scale by the impacting action of a reciprocating piston. They are used where there is a need to break through heavy and stubborn layers of rust or chemical coatings.



Variants

Tungsten Tip
Standard Tip



Approvals and Certifications

All Teryair Scabblers are CE marked
and manufactured under an ISO
9001:2015 Quality system – SGS.

Main Features of 3SC Triple Scabblers

- Lever type throttle.
- Special tungsten carbide tipped piston material
- Simple one moving part mechanism
- Easy to maintain
- Light weight
- Easy to manoeuvre.

Application of 3SC Triple Scabblers

- Removal of heavy and stubborn layers of rust
- Removal of hard chemical coatings.

Technical Data

Teryair Model No		3SC
<i>IMPA Code</i>		59 03 83
<i>Maximum operating pressure</i>		6kg/cm ² (90 psi)
<i>Air Consumption (No Load)</i>	<i>CFM</i>	15
	<i>m³/ min.</i>	0.42
<i>No. of Piston</i>		3
<i>Piston Diameter</i>	<i>mm</i>	27
<i>Piston Length</i>	<i>mm</i>	111
<i>Piston Stroke</i>	<i>mm</i>	26.2
<i>Blows per min</i>	<i>BPM</i>	3 x 2400
<i>Sound Power Level (Load)</i>	<i>LwA db(A)</i>	111.3
<i>Vibration Level Primary</i>	<i>m/s²</i>	8.7 (k)
<i>Mass (Weight)</i>	<i>Kg</i>	5.7
<i>Thread Size of Air Inlet</i>		1/2" BSP

Optional Accessories

Part No	Description	Qty
121 21 02	SINGLE PIECE PISTON	3
121 21 20	INTEGRAL PISTON (SHORT LENGTH)	3
121 21 21	NON SPARK PISTON	3