



Teryair pneumatic drills have a high power to weight ratio and are comfortable to handle for long working hours. Four models covering up to 13mm in steel. Drill chucks are supplied as standard equipment. Minimum vibration during drilling operations, quiet operation thanks to precision gearing.

Features

- Low vibration. • High power to weight ratio.
- Reversible.

Quick connect coupler 20 PM.
Steady handle (PD13PG only) .
Drill Chucks and key.

Standard equipment included

Applications

For light and medium duty drilling.

Technical data

CH26R





PD13PG

Package dimensions & weight

| IMPA Code | Teryair Model No | Drilling Capacity mm | Collect Chuck Size mm | Free Speed rpm | Air Inlet PT | Air Hose mm | Net Weight kgs | Teryair Model No | Weight kgs | Box Dimensions cms |
|--------------|---------------------|----------------------------|-----------------------------|----------------------|--------------------|-------------------|----------------------|---------------------|----------------------|--------------------------|
| 590341 | PD6PG | 6.5 | 6.5 | 2900 | 1/4 | 9.5 | 1.1 | PD6PG | 1.5 | 22 x 20 x 8 |
| 590342 | PD10PG | 9.5 | 10.0 | 1400 | 1/4 | 9.5 | 1.1 | PD10PG | 1.5 | 22 x 20 x 8 |
| 590346 | PD8PG | 8.0 | 8.0 | 1500 | 1/4 | 9.5 | 1.1 | PD8PG | 1.5 | 22 x 20 x 8 |
| 590347 | PD13PG | 13.0 | 13.0 | 700 | 3/4 | 9.5 | 1.7 | PD13PG | 2.0 | 22 x 20 x 8 |

Pneumatic Chipping Hammers -10mm Round Chuck

These pneumatic chipping hammers are the perfect tool for any light duty chipping work such as the removal of unwanted material like concrete, tiles, rust, dirt from the base material surface. A variety of chisels are available for different applications Chisels as shown are part of standard equipment.

Features

- Hard hitting and high frequency of blows
- AccePts universally available 10mm shank accessories

Applications

Standard equipment included

For removal of paint, rust, calking/ weld flux, for billet chipping and general chipping

- Moil point tool. • Chisel point tool 3 nos.
- Quick connect coupler 20 PM.



CH23R

Technical data

| IMPA Code | Teryair Model No | Type of Shank | Blows per minute | Piston Dia mm | Air Inlet PT | Air Hose mm | Weight kgs |
|--------------|------------------------|------------------|------------------------|---------------------|--------------------|-------------------|----------------------|
| 590361 | CH26R | Round | 2600 | 19.0 | 3/8 | 9.5 | 1.5 |
| 590362 | CH23H | Round | 2300 | 18.0 | 1/4 | 9.5 | 2.0 |

Package dimensions & weight

| Teryair Model No | Weight kgs | Box Dimensions cms | | |
|---------------------|----------------------|--------------------------|--|--|
| CH26R | 1.7 | 22 x 20 x 8 | | |
| CH23H | 2.1 | 22 x 20 x 8 | | |